

6JE6

Beam Power Tube

NOVAR TYPE

For Color-TV Horizontal-Deflection Amplifier Applications

GENERAL DATA

Electrical:

Heater Characteristics and Ratings:

Voltage (AC or DC)	6.3 ± 0.6	volts
Current at heater volts = 6.3	2.500	amp
Peak heater-cathode voltage:		
Heater negative with		
respect to cathode	200 max.	volts
Heater positive with		
respect to cathode	200 ^a max.	volts

Direct Interelectrode Capacitances

(Approx.): ^b		
Grid No.1 to plate	0.44	pf
Grid No.1 to cathode, grid No.3,		
grid No.2, and heater	21.0	pf
Plate to cathode, grid No.3,		
grid No.2, and heater	11.0	pf

Characteristics, Class A₁ Amplifier:

	Triode Connection	Pentode Connection	
Plate Voltage	125	70 175	volts
Grid No.3	Connected to cathode at socket		
Grid-No.2 Voltage	125	125 125	volts
Grid-No.1 Voltage	-25	0 -25	volts
Amplification Factor	3.3	- -	
Plate Resistance (Approx.)	-	- 5500	ohms
Transconductance	-	- 10500	μmhos
Plate Current	-	580 ^c 115	ma
Grid-No.2 Current	-	40 ^c 5	ma
Grid-No.1 Voltage (Approx.)			
for plate ma. = 1	-	- -55	volts

Mechanical:

Operating Position	Any
Type of Cathode	Coated Unipotential
Maximum Overall Length	4.600"
Seated Length	4.090" ± 0.130"
Diameter	1.438" to 1.562"
Bulb	T12
Cap	Small (JEDEC No.C1-1)
Socket	Cinch Mfg. Co. No.149 19 00 033, Industrial Electronic Hardware Corp. No.S0-0968-SL1, or equivalent




RADIO CORPORATION OF AMERICA
Electron Tube Division
Harrison, N. J.

DATA 1
4-63

6JE6

Base. Large Button Novar 9-Pin (JEDEC No.E9-76)
 Basing Designation for BOTTOM VIEW. 9QL

Pin 1-Grid No.2
 Pin 2-Grid No.1
 Pin 3-Cathode
 Pin 4-Heater
 Pin 5-Heater



Pin 6-Grid No.1
 Pin 7-Grid No.2
 Pin 8-Grid No.3
 Pin 9-Do Not Use
 Cap-Plate

HORIZONTAL-DEFLECTION AMPLIFIER

Maximum Ratings, Design-Maximum Values:

For operation in a 525-line, 30-frame system^d

DC PLATE-SUPPLY VOLTAGE	990 max.	volts
PEAK POSITIVE-PULSE PLATE VOLTAGE ^a	7000 max.	volts
PEAK NEGATIVE-PULSE PLATE VOLTAGE	1100 max.	volts
DC GRID-No.3 VOLTAGE (See <i>Operating Considerations</i>).	75 max.	volts
DC GRID-No.2 (SCREEN-GRID) VOLTAGE. . . .	190 max.	volts
PEAK NEGATIVE-PULSE GRID-No.1 (CONTROL-GRID) VOLTAGE.	250 max.	volts
CATHODE CURRENT:		
Peak.	1100 max.	ma
Average	315 max.	ma
GRID-No.2 INPUT	3.2 max.	watts
PLATE DISSIPATION ^f	24 max.	watts
BULB TEMPERATURE (At hottest point on bulb surface). . . .	240 max.	°C

Maximum Circuit Values:

Grid-No.1-Circuit Resistance:

For grid-resistor bias operation ^f	0.47 max.	megohm
For plate-pulsed operation (horizontal-deflection circuits only). . . .	10 max.	megohms

^a The dc component must not exceed 100 volts.

^b Without external shield.

^c This value can be measured by a method involving a recurrent wave form such that the plate dissipation, grid-No.2 input, and cathode current will be kept within ratings in order to prevent damage to the tube.


^d As described in "Standards of Good Engineering Practice Concerning Television Broadcast Stations", Federal Communications Commission.

^e This rating is applicable where the duration of the voltage pulse does not exceed 15 per cent of one horizontal scanning cycle. In a 525-line, 30-frame system, 15 per cent of one horizontal scanning cycle is 10 microseconds.

^f It is essential that the plate dissipation be limited in the event of loss of grid signal. For this purpose, some protective means such as a cathode resistor of suitable value should be employed.



6JE6



ALL DIMENSIONS IN INCHES

** APPLIES IN ZONE STARTING 0.375" FROM BASE SEAT.

OPERATING CONSIDERATIONS

In *horizontal-deflection amplifier service* a positive voltage may be applied to grid No.3 to minimize "snivets" interference which may occur in both uhf and vhf television receivers. A typical value for this voltage is 30 volts.




RADIO CORPORATION OF AMERICA
Electron Tube Division
Harrison, N. J.

DATA 2
4-63

6JE6

AVERAGE CHARACTERISTICS




RADIO CORPORATION OF AMERICA
 Electron Tube Division

Harrison, N. J.



6JE6

AVERAGE CHARACTERISTICS



RADIO CORPORATION OF AMERICA
 Electron Tube Division
 Harrison, N. J.

DATA 3
 4-63